



I. DIMENSIONS

- A. Lengths: 8'6", 9'6", 10'6", 12'6", 14'6", 16'6" and 18'6"
- B. Widths: 88", 96" and 102"

II. SIDE RACKS

- A. Height: 14"
- B. Construction - 12 ga. (.105") skin sheet welded to 13 ga. (.09") hat section stakes.
 - formed tarp rail at top.
 - 12 ga. (.105") "C" shaped rear corner posts.

III. TAILGATE - SINGLE ACTING

- A. Height: 14"
- B. Construction - 12 ga. (.105") skin sheet welded to 12 ga. (.105") support posts.
 - hinged at bottom with 3/8" hinge brackets.

IV. FRONT

- A. Standard 40" high drop-in bulkhead included. See bulkhead specification sheet for details.

V. PAINT

- A. Black Acrylic E-Coat

Pre-Paint Preparation and Topcoat – Electrocoat Process

*All product goes through a multi-stage immersion cleaning and rinsing process to thoroughly clean all surfaces.

*The product is then immersed in a chemical bath to prep the steel for optimum zinc phosphate adhesion prior to immersion in the zinc phosphate tank.

*The zinc phosphate stage then puts a base zinc crystalline structure on the steel for superior paint adhesion.

*A subsequent sealer rinse tank seals the pretreated surface to optimize corrosion resistance.

*Two reverse osmosis rinse tanks insure the product is free from mineral deposits prior to painting.

*The product is then immersed in an acrylic electro – deposition tank when a high gloss black acrylic topcoat is charged onto the product.

*After two final permeate rinse tanks remove any excess acrylic material and insure a consistent surface finish, the product is oven cured at 350 degrees to fully crosslink and cure the electrocoat topcoat providing an extremely durable and rust resistant finish.



VI. CONTRACTOR RACK WEIGHTS

Body Dimensions	Weight
10'6" x 96"	388 lbs.
12'6" x 96"	404 lbs.
14'6" x 96"	418 lbs.
16'6" x 96"	438 lbs.
18'6" x 96"	464 lbs.
20'6" x 96"	480 lbs.
22'6" x 96"	496 lbs.

* For installation on Heavy Duty Platforms